

NATUR LED OIL Gloss 1389-0040

DESCRIPTION

Product description

NATUR LED OIL Gloss 1389-0040 is an LED-curing OIL for rolling, which can be used on industrial rolling mills as well as on construction sites. It is an environmentally friendly, practically solvent-free LED OIL. NATUR LED OIL 1389-0040 can be used to create natural furniture and parquet surfaces with a pronounced oil character. Particularly noteworthy are the pleasant feel and the ability to enhance the original beauty of the wood.



- Interior finishing

Certificates, standards & Product properties



DIN EN 71-3 (Toy safety - migration of certain elements)

DIN 68861-1B (Durability of furniture surfaces)

PAK-Werte (PAK testing according to AfPS GS 2014:01)

Complies with the Decopaint / VOC Directive



GISCODE

-

Colors

colorless

Product group

Oil

Technical data

Viscosity: ~30 sec. in DIN 6 cup / 20 °C

PROCESSING



Smooth hard rubber roller and then spreader pad / brush

Application quantity

5-25 g/m²

Construction site / On site

Apply the oil by hand on site, spread evenly with a roller and work in with a PAD / brush

Dilution

-

DRYING



Curing: 1 x LED spotlight (395) min. 14 W/cm² V=7 - 10 m/min

SUBSTRATE

Substrate type

Softwood, hardwood, veneer

Preparation

Dry wood, free from grease, silicones and oils.
Free from sanding dust and other soiling.

Basic grinding

Sand with 120 - 180 grit and dust off

APPLICATION EXAMPLE

System

Base oil:
1x roll 20-25 g/m² and spread with pad/brush
Curing 1x LED spotlight(395) min. 14W/cm² V=7-10m
Smooth with 320 grit

Top oil:
1x 5-7 g/m² roll and spread with pad/brush
Curing 1x LED spotlight (395) min. 14W/cm² V=7-10m

ORDER INFORMATION

Container sizes	20 l 4 x 2,5 l	
Minimum purchase	-	
Gloss level	1380-0040 -> Ultramatt 1389-0040 -> Gloss	1385-0040 -> Semi Gloss
Shelf life / storage	Can be stored for approx. 6 months in the sealed original container. Store frost-free and at room temperature (max. 30 °C).	

Additional products	Name NATUR REAKTIV VERDÜNNER	Article number 9100-0022
Cleaning of tools	REINIGUNGSVERDÜNNUNG for rolling	9800-0010

WEITERE HINWEISE

Notes

As with all reactive oils, a particularly clean working method is recommended.

Stir well before use.

The product must be protected from light during storage and processing!

Always apply a test coating!

The containers must always be tightly closed after use.

Technical safety Specifications

Further information on safety during transportation, storage and handling well as disposal can be found in the corresponding safety data sheet.